Product datasheet

Specification





Residual current circuit breaker (RCCB), Domae, 2P, 63A, AC type, 30mA

16791

! Discontinued on: 31 Jul 2023

! Discontinued

Main

Range	Domae	
Product or component type	Residual current circuit breaker (RCCB)	
Device short name	RCCB	
poles description	2P	
Earth-leakage protection class	Type AC	

Complementary

Neutral position	Left
Device location in system	Outgoer
[In] rated current	63 A
network type	AC
network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to IEC 61008
Residual current tripping technology	Electromechanical
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Rated breaking and making capacity	Im = 630 A
Rated conditional short-circuit current	6 kA 63 A
[Ui] rated insulation voltage	440 V
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
mounting mode	Fixed
mounting support	35 mm symmetrical DIN rail
Connection pitch	18 mm between phase and neutral
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	76 mm

Connections - terminals

Tunnel type terminals (downstream) 25 mm² flexible

Tunnel type terminals (downstream) 35 mm² rigid

Tunnel type terminals (upstream) 25 mm² flexible

Tunnel type terminals (upstream) 35 mm² rigid

Environment

Standards	IEC 61008
Pollution degree	2
Tropicalisation	2 conforming to IEC 61008
Operating altitude	2000 m
Ambient air temperature for operation	-540 °C
Ambient air temperature for storage	-4060 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.4 cm
Package 1 Width	9.0 cm
Package 1 Length	3.8 cm
Package 1 Weight	210 g
Unit Type of Package 2	S03
Number of Units in Package 2	54
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	11.781 kg
Unit Type of Package 3	P12
Number of Units in Package 3	432
Package 3 Height	44.4 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	106.248 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations