

Product details page



P 17 TEMPRA LEGRAND

Surface mounting socket P17 - IP66/67 - 380/415 V~ - 32 A - 3P+N+E

REF. 555459 | EAN. 3245065554595

> [The product details page](#)

Caractéristiques techniques

- P 17 Tempra Pro IP 66/67 LV 16 and 32 A Surface mounting sockets - Two possible angles (5° or 25°) 380/415 V~ - 32 A - 3P+N+E

CEE socket outlet 16 A	None
CEE socket outlet 32 A	1x32A5p400V
CEE socket outlet 63 A	None
CEE socket outlet 125 A	None
Number of socket outlets with protective contact CEE 7/3 (type F)	1
Protection	None
Earth leakage switch	None
Number of miniature circuit breakers (MCB)	0
Housing material	Plastic

Power supply/connection possibility	Other
Diameter cable entry	M32
Handling	Wall mounting
Degree of protection (IP)	IP67
Military model	No
Colour	Grey
Height	163 mm
Width	113 mm
Depth	162 mm

document title

TECHNICAL DOCUMENTATION

- F01811FR-02.pdf | PDF (3.67Mo)
- LE05815AA-01.pdf | PDF (2.53Mo)
- F01811EN-03.pdf | PDF (9.37Mo)
- CAD & Design specs / BIM
- Prises_non_verrouillées_saillies_380_415V.rfa | RFA (1.47Mo)
- 555459.dwg | DWG (0.13Mo)
- surface_no_interlocked_sockets_380_415V.rfa | RFA (1.47Mo)

CATALOGUE PAGE & OTHERS

- ex223001_0527.pdf | PDF (0.11Mo)
- ex223001_0533.pdf | PDF (0.07Mo)
- ex223001_0534.pdf | PDF (0.06Mo)
- Agreements & Certificates
- IMQ-CA02.05951 | (0.42Mo)
- OC / CB-FR_710665 | (0.7Mo)
- LGRP-2014-112-V1-EN.pdf | PDF (1.02Mo)

