

Product sheet



ARTEOR™ LEGRAND

Socket Arteor - German - 16 A - 2P+E shuttered - 2 modules - orange

REF. 572460 | EAN. 3245065724608

> [Visit e-catalogue](#)

Product characteristics

- Arteor™ - international socket outlets - Mechanisms supplied with rocker plates , to be equipped with support frames and plates
- German standard socket outlets 16 A - 2 modules 2P+E shuttered for child safety - Dedicated orange - Can be installed in receptacles for floor sockets

Technical characteristics

Model	Socket outlet CEE 7/3 (type F)
Protective contact	Other
Number of active contacts (round)	1
Number of active contacts (flat)	0
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of units	1
Number of modules (module system)	2
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	Other
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No

Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	Orange
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP40
Degree of impact strength (IK)	IK04
Device width	45 mm
Device height	45 mm
Device depth	40 mm
Compatible with Apple HomeKit	No

Colour	Orange
RAL-number (similar)	2003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	Yes
With function lighting	No
Over voltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	No special power supply
Mounting method	Module frame
Type of fastening	Snap mounting (engagement)
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes

Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	31.5 mm
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section	4-4 mm ²
Cable support	Other
Cover	Central cover plate
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

- F00723EN-05.pdf | PDF (1.07Mo)
- F00723FR-05.pdf | PDF (1.07Mo)

Agreements & Certificates

- OC / CB-HU-001259-A4/M1 | (0.12Mo)
- LGRP-01719-V01.01-EN.pdf | PDF (0.73Mo)
- OC / CB-HU-001259-A1 | (0.54Mo)
- SNI-824 220215 | (1.19Mo)
- OC / CB-HU-003962 | (0.48Mo)

CATALOGUE PAGE & OTHERS

- ex223001_0574.pdf | PDF (0.11Mo)