

Product datasheet

Specifications



Easy UPS 3M 120kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS120KHS

Overview

Presentation Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 120 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 400 V 3 phases

Product or component type Uninterruptible power supply (UPS)

Other Input Voltage 380 V
415 V

Main Output Voltage 400 V 3 phases

Other Output Voltage 380 V
415 V

Rated power in W 120 kW

Rated power in VA 120 kVA

Provided equipment Dust filter
Installation guide
Start-up service

Range of product Easy UPS 3M

Batteries & Runtime

Efficiency [View Efficiency Graph](#)

Battery type External battery system

Number of battery filled slots 0

Number of battery free slots 0

Physical

Colour White (RAL 9003)

Height 130 cm

Width 50 cm

Depth 85 cm

Net weight 193 kg

USB compatible Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input

Maximum input current	207 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging without derating
Input Power Factor at Full Load	0.99
Input voltage limits	342...477 V
Network frequency	40...70 Hz

Output

Maximum configurable power in VA	120 kVA
Maximum configurable power in W	120 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Output voltage tolerance	+/- 1 %
UPS type	Double conversion online
Wave type	Sine wave

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...4921 ft
Ambient air temperature for storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.000000000...15240.000000000 m
Acoustic level	72 dBA
Heat dissipation	20473 Btu/h
IP degree of protection	IP20

Communications & Management

control panel	Touch screen LCD user interface
---------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	150.000 cm
Package 1 Width	97.500 cm
Package 1 Length	62.500 cm
Package 1 Weight	223.000 kg

Contractual warranty

Warranty

1 year on-site repair or replace with factory authorized Start-Up

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **151003**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#) **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**