

# Product datasheet

Specifications



## New Unica - buzzer - 2 modules - white

NU378518

### Main

|                                |                   |
|--------------------------------|-------------------|
| Range                          | New Unica         |
| device application             | Signalling        |
| product or component type      | Buzzer            |
| Device presentation            | Mechanism         |
| [Ue] rated operational voltage | 230 V AC 50/60 Hz |
| Number of modules              | 2 modules         |
| Fixing mode                    | Clip-in           |
| Colour tint                    | White (RAL 9003)  |

### Complementary

|                                       |   |
|---------------------------------------|---|
| Current consumption                   | 40 mA   |
| Type of setting                       | Volume can be adjusted using a screw  |
| Device mounting                       | Flush   |
| Operating time                        | <= 30 ms  |
| Connections - terminals               | Screw terminals   |
| Acoustic level                        | Between 76 and 80 dB  |
| Cable cross section                   | 0.75...1.5 mm² flexible cable<br>0.75...1.5 mm² rigid cable                             |
| Material                              | Thermoplastic ABS-UV stabilised: mechanism rocker<br>PC (polycarbonate) GF10 FR: casing |
| Standards                             | EN 62080<br>CE  |
| Directives                            | 2014/35/EU - low voltage directive  |
| Ambient air temperature for operation | 15...30 °C  |
| Ambient air temperature for storage   | 0...35 °C   |
| Embedding depth                       | 31 mm   |
| Depth                                 | 50 mm   |
| Width                                 | 45 mm   |
| Height                                | 45 mm   |
| Net weight                            | 0.091 kg  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                               |   |
|-------------------------------|---|
| Resistance to chemical agents | Resistant to alcohol (70 %)               |
|                               | Resistant to alcohol (96 %)               |
|                               | Resistant to A-Lactic Acid                |
|                               | Resistant to diluted quaternary ammonium  |
|                               | Resistant to diluted bleach               |
|                               | Resistant to diluted ammonia              |
|                               | Resistant to soapy water                  |
|                               | Resistant to crystal cleaner              |
|                               | Resistant to hydrogen peroxide 10 volumes |
|                               | Resistant to hexane                       |

## Environment

|                         |      |
|-------------------------|------|
| IK degree of protection | IK04 |
| IP degree of protection | IP20 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 4.500 cm  |
| Package 1 Width              | 4.500 cm  |
| Package 1 Length             | 5.000 cm  |
| Package 1 Weight             | 51.000 g  |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 5.600 cm  |
| Package 2 Width              | 14.000 cm |
| Package 2 Length             | 26.000 cm |
| Package 2 Weight             | 587.000 g |
| Unit Type of Package 3       | S02       |
| Number of Units in Package 3 | 50        |
| Package 3 Height             | 15.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 3.238 kg  |

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Sustainable Packaging

## Resource performance

✔ Sustainable Packaging

## Well-being performance

✔ Reach Free Of Svhc

✔ Toxic Heavy Metal Free

✔ Mercury Free

✔ Rohs Exemption Information      Yes

Reach Regulation      [REACH Declaration](#)

Eu Rohs Directive      Compliant  
[EU RoHS Declaration](#)

China Rohs Regulation      [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

Weee      The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins