

Product datasheet

Specifications



Emergency luminaire, Exiway Light, Standard, selectable duration, 110lm, IP65, white

OVA44011

Main

Range	Exiway
Product Name	Exiway Light
Product Or Component Type	Emergency luminaire
Device Application	Anti-panic lighting
Function	Standard
Operational Mode	Maintained Non-maintained
Number Of Batteries	1 x 3.2 V 0.57 Ah LiFePO4
Light Source	9 x LED 0.3 W
Visibility Distance	20 m
Light Source Colour	Neutral
Wiring Device Additional Information	2 wires connection

Complementary

[Ue] Rated Operational Voltage	230 V AC 50/60 Hz
Power Consumption In Va	11.5 VA non-maintained 11.1 VA maintained
Power Consumption In W	0.4 W non-maintained 0.8 W maintained
Electrical Insulation Class	Class II
Led Lifespan	100000 h
Test Function	Manual
Autonomy	1 h 1.5 h 2 h 3 h
Charging Time	12 h
Luminous Flux	Emergency condition: 110 lm for 1 h Emergency condition: 90 lm for 1.5 h Emergency condition: 70 lm for 2 h Emergency condition: 50 lm for 3 h Maintained mode: 70 lm
Local Signalling	LED
Device Mounting	Surface wall Surface ceiling
Material	Polycarbonate self-extinguishing

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	112 mm
Depth	32 mm
Width	229 mm
Net Weight	0.35 kg

Environment

Ip Degree Of Protection	IP65
Ik Degree Of Protection	IK09
Fire Resistance	850 °C
Product Certifications	CE ENEC
Ambient Air Temperature For Operation	0...40 °C
Standards	EN 60598-1: II EN 60598-2-22 EN 62471 UL 94 V2

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	12 cm
Package 1 Length	23.5 cm
Package 1 Weight	390 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	18
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.459 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	144
Package 3 Height	45 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	71.672 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)