





APC Essential SurgeArrest 5 Outlet 2 USB Ports Black 230V Germany

PME5U2B-GR

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	220 V 230 V
	240 V
Input Connection Type	Schuko CEE 7/7P
Cable Length	1.52 m
Number Of Cables	1
Provided Equipment	User manual

Physical

Colour	Black	
Height	4 cm	
Width	33.5 cm	
Depth	6.3 cm	
Net Weight	0.5 kg	
Mounting Preference	No preference	
Mounting Mode	Not rack-mountable	

Input

Input Power	2300 W	
Network Frequency	50/60 Hz	
Switching Current Capacity	10 A	

Output

Number Of Power Socket Outlets	5	
Outlet Standard	Schuko CEE 7	

Conformance

Product Certifications	CE
Marking	CE Mark

Environmental

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-1545 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

Surge Protection and Filtering

Response Time	1 ns common mode	
Common Mode Rejection	45 dB	
Peak Current	15 kAnormal mode	
Surge Energy Rate	680 J	

Packing Units

•		
Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	5 cm	
Package 1 Width	12 cm	
Package 1 Length	36.5 cm	
Package 1 Weight	607 g	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	12	
Package 2 Height	27.5 cm	
Package 2 Width	30 cm	
Package 2 Length	39 cm	
Package 2 Weight	7.84 kg	
Scc14	10731304347054	

Contractual warranty

Warranty 20 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information