



Function	Use either as an emergency luminaire or exit sign
Testing system	Stand Alone
Housing	Polycarbonate, Glow wire test : 850°C, RAL9003
Type of mounting	Surface Options : Recessed base for ceiling, double sided cone diffuser, plexi plate diffuser, set of 3 exit legends (L, R, D)
Terminals	up to 1x2,5 mm ² per connection
Degree of protection	IK04, IP42 or IP65
Operation Mode	Non Maintained or Maintained & Non Maintained mode selectable
Connection voltage	230V +/- 5% [220V-240V] 50-60Hz
Permissible ambient temperature	+5°C to +40°C
Battery	Ni-Cd
Light source	LED strip
Duration	3 hours
Viewing distance	20m or 30m
Insulation class	II
Dimensions in mm	20 m viewing distance version: 270 x 119 x 49 30 m viewing distance version: 371 x 170 x 62

Ordering details

Order code	Description
SL2NM42C3	SL20,NM,IP42,60lm,3H
SL2NM42D3	SL20,NM,IP42,100lm,3H
SL2NM42F3	SL20,NM,IP42,200lm,3H
SL2NM65D3	SL20,NM,IP65,100lm,3H
SL2MNM42C3C	SL20,MNM,IP42,60lm,3H
SL2MNM42D3C	SL20,MNM,IP42,100lm,3H
SL2MNM65C3C	SL20,MNM,IP65,60lm,3H
SL2MNM65D3C	SL20,MNM,IP65,100lm,3H
SL2MNM42D3D	SL20,MNM,IP42,100lm,3H
SL3MNM42F3C	SL30,MNM,IP42,200lm,3H
SL3MNM65F3C	SL30,MNM,IP65,200lm,3H

Eaton is constantly striving to ensure reliable, efficient and safe power supply wherever needed. Thanks to their unparalleled knowledge about power management in different sectors, Eaton's experts create integrated and customised solutions that can overcome the toughest challenges.

Our goal is to provide the best solution for every application. However, decision makers want much more than just innovative products; that's why they choose Eaton, which resolutely strives to assist them, putting the success of the customer first.

For more information and to find your contact person, visit www.eaton.com

We reserve the right to make any changes to the products and information contained herein, as well as to errors and omissions. Only the order confirmations and Eaton technical documentation are binding. Furthermore, photos and images do not guarantee a specific layout or functionality. Their use in any form is subject to prior approval by Eaton. The same applies to brands (especially Eaton, Moeller, Cutler-Flammer and CEAG)

Eaton is a registered trademark.

All other trademarks are the property of their respective owners.

Eaton Industries Manufacturing GmbH

Electrical Sector EMEA
Route de la Longeraie, 7
1110 Morges, Switzerland
Eaton.eu

Middle East

Eaton FZE

Plot No. TP010505, Technopark
P.O. Box 261768
Dubai, United Arab Emirates
Tel. +971 4 8066100
Fax : +971 4 8894813

© 2016 Eaton
All Rights Reserved
Printed in U.A.E.

November 2016

SafeLite Product overview

Simply safe



Simply safe



Recessed version

Features & Benefits

- Compliant with EC standards
- EN compliance
- All applications covered (Escape route, Anti-panic, Exit sign)
- One product throughout installation for same look and feel across the building
- Accessories available for a better integration in all buildings
- Easily installed as retro fit due to good performance ensuring scheme compliance
- 3h Duration
- 20m and 30m viewing distance versions available
- Latest generation LEDs with high lumen/watt ratio

Accessories

Double side diffuser:

Cone diffuser used to do ceiling signage, double or single side (blind picto inside).
In accordance with EN1838 standard.
Exit pictograms comply with ISO7010.

Compatible with IP42 and IP65 luminaire versions.

Could be associated with recessed base.

Pictograms have to be ordered separately (or re use ones delivered with luminaires).



Plexi plate diffuser:

Used to do ceiling signage, double or single side.

Exit pictograms comply with ISO7010.
Select order code according to signage configuration requested.

Compatible with IP42 and IP 65 luminaire versions.

Could be associated with recessed base.



Recessed base:

Option used for full recessed mounting.
Compatible with IP42 and IP65 luminaire versions.

Could be associated with double side diffuser.



Other specific pictograms available upon request



Accessories

SL23A	20m adhesive pictograms (L,R,D)
SL33A	30m adhesive pictograms (L,R,D)
SL23I	20m 3x Foils to insert inside the luminaire (L, R, D)
SL33I	30m 3x Foils to insert inside the luminaire (L, R, D)
SL3PPD	30m Plexi Plate 1 side down
SL3PPDD	30m Plexi Plate 2 sides down
SL3PPLR	30m Plexi Plate 2 sides L,R
SL2PPD	20m Plexi Plate 1 side down
SL2PPDD	20m Plexi Plate 2 sides down
SL2PPLR	20m Plexi Plate 2 sides L,R
SL2CD	SL20,Cone Diffuser*
SL3CD	SL30, Cone Diffuser*
SL2RB	SL20,Recessed Base, Plastic, RAL9003
SL3RB	SL30,Recessed Base, Plastic, RAL9003

*Pictograms have to be ordered separately