



Smartbright Waterproof G3 WT068C

WT068C NW LED36 L1200 PSU

-

Philips Smartbright Waterproof G3 batten offers exceptional value. It is Perfect for everyday lighting installations. Available in 3 standard sizes, it has option of Standard and through wiring version.


Product data

General Information		Controls and Dimming	
Light source color	840 neutral white	Dimmable	No
Optical cover/lens type	-	Mechanical and Housing	
Control interface	-	Housing Material	Polycarbonate
Protection class IEC	Safety class II	Optical cover/lens material	Polycarbonate
CE mark	CE mark	Optical cover/lens finish	Opal
Number of products on MCB of 16 A type B 1		Overall length	1188 mm
Light source engine type	LED	Overall width	69 mm
Operating and Electrical		Overall height	74 mm
Input Voltage	220 to 240 V	Color	White and gray
Input Frequency	50 or 60 Hz	Approval and Application	
Power Factor (Min)	0.9	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]

Smartbright Waterproof G3 WT068C


Mech. impact protection code	IK06 [1 J]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial input power	33 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-20 to +45 °C

Product Data	
Full product code	871016336063899
Order product name	WT068C NW LED36 L1200 PSU
EAN/UPC - Product	8710163360638
Order code	911401881780
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881780
Net Weight (Piece)	0.490 kg



Dimensional drawing

WT068C-4ft



Dust/ water protected LED

