

Product datasheet

Specifications



Exiway Easyled- emergency light luminaire - std - non-maintained - 3 h - 120 lm

OVA38353

! Discontinued on: Jun 19, 2023

! Discontinued

Main

Range	Exiway
Aesthetic Name	Exiway Easyled
Product Or Component Type	Emergency light fitting
Device Application	Lighting
Function	Standard
Supply	Non-maintained
Number Of Batteries	1 x 4.8 V 1.6 Ah Ni-Cd (Nickel-Cadmium)
Colour	White
Light Source	LED integral LED 4 x 1.5 W
Light Source Colour	White
Cover Type	Transparent
Wiring Device Additional Information	Can be inhibited with rest mode via Teleur range of remote controls

Complementary

[Ue] Rated Operational Voltage	220...230 V AC 50/60 Hz
Power Consumption In Va	3.9 VA
Power Consumption In W	1 W
Current Consumption	16 mA
Electrical Insulation Class	Class II
Autonomy	3 h
Charging Time	12 h
Luminous Flux	Emergency condition: 120 lm
Type Of Glass	Serigraphed transparent glass
Material	Plastic: housing Plastic: cover
Device Mounting	Flush wall Surface wall Surface ceiling Flush false ceiling
Height	37 mm
Width	292.5 mm
Depth	116.5 mm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	0.57 kg
------------	---------

Environment

Ip Degree Of Protection	IP42
-------------------------	------

Ik Degree Of Protection	IK07
-------------------------	------

Ambient Air Temperature For Operation	5...30 °C
---------------------------------------	-----------

Fire Resistance	850 °C
-----------------	--------

Product Certifications	ENEC
------------------------	------

Standards	EN/IEC 60598-2-22 IEC 60695-2-10
-----------	-------------------------------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	4.5 cm
------------------	--------

Package 1 Width	12.5 cm
-----------------	---------

Package 1 Length	30 cm
------------------	-------

Package 1 Weight	626 g
------------------	-------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)
