

# Product data sheet

## 6106-1 CT

EAN-No. 4000896173167



Length: 197 mm · Torque range min-max: 1 – 6 Nm · Accuracy: 4 % ·  $\frac{63}{16}$



- Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- **Accuracy  $\pm 2\%$  of the scale value** (6106-1CT:  $\pm 4\%$ ) (in direction of actuation for right-hand tightening)  
For left-hand tightening, use our torque wrenches with insert tool
- Application: engines, gearboxes, machinery, industry, model making
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output:  $\frac{63}{16}$
- Dimensions: 197 mm
- Net weight: 0.3 kg
- For manual operation
- Torque range min-max: 1 – 6 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.1 Nm
- Actuating force min.-max. kg: 0.7 – 4.4 kg
- Number of teeth: 90 (Opening angle 4°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Torque tools in industry

Order Number

6106-1 CT