

Specifications



Photo is representative



Eaton 9E6KI

Eaton 9E UPS, 6000 VA, 4800 W, Input: Hardwired, Output: Hardwired, Tower

General specifications

PRODUCT NAME	Eaton 9E UPS
CATALOG NUMBER	9E6KI
UPC	743172067661
PRODUCT LENGTH/DEPTH	61.29 cm
PRODUCT HEIGHT	70.85 cm
PRODUCT WIDTH	26.24 cm
PRODUCT WEIGHT	68 kg
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC

Additional information

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
CONSTRUCTION TYPE	Free standing model
EFFICIENCY AT MAX. LOAD	91
HOT SWAP POWER	No
INTERNAL BYPASS	Yes
PACKAGE CONTENTS	• UPS • USB cable • Serial cable • User manual
PHASE (INPUT)	1
PHASE (OUTPUT)	1
RACK MOUNTING KIT	No

Communication

COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini-terminal block for remote power off • Communication slot
ETHERNET INTERFACE	No
EXPANSION SLOTS	One slot for optional communication card
INCLUDES NETWORK CARD	No
POTENTIAL FREE SWITCH CONTACT	Yes
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
TYPE OF INTERFACE	Other
USER INTERFACE	LCD Display

Battery specifications

BATTERY MANAGEMENT	• Automatic battery test • Deep discharge protection
---------------------------	--

BATTERY QUANTITY	15
BATTERY RATING	12 V / 9 Ah
BATTERY REPLACEMENT	Replacable batteries
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME GRAPH	View runtime graph

Electrical input

INPUT CONNECTION	Hardwired/fixed connection
INPUT FREQUENCY RANGE	45-66Hz
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
INPUT POWER FACTOR	>.99
INPUT VOLTAGE RANGE	176-276 V (110-276 V with derating)
NOMINAL FREQUENCY	50/60 Hz

Electrical output

FEED TYPE	1
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
OUTPUT POWER FACTOR	0.8
OUTPUT VOLTAGE RANGE	220/230/240 V +/- 2%
OUTPUT WAVEFORM	Sine wave
TOPOLOGY	Online/Double-conversion
VA RATING	6000 VA
VOLTAGE	230V
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	3
WATTAGE	4800 W

Environmental

ALTITUDE	3000 m
NOISE LEVEL	<55 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Resources

COMPLIANCE INFORMATION	EU declaration of conformity Eaton 9E UPS
DECLARATIONS OF CONFORMITY	EU Declaration of Conformity
MANUALS AND USER GUIDES	Eaton 9E UPS - Installation and user manual Eaton 9E UPS - User Manual
TECHNICAL DATA SHEETS	Eaton 9E UPS - Datasheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

