

Regulated Power Supply, 100-240V AC, 24V 5 A, single phase, Optimized

ABLS1A24050

Main

Range of product	Modicon Power Supply
Product or component type	Power supply
Power supply type	Regulated switch mode
Variant option	Optimized
Enclosure material	Aluminium
Nominal input voltage	100240 V AC single phase 100240 V AC phase to phase 140340 V DC
Rated power in W	120 W
Output voltage	24 V DC
Power supply output current	5 A

Complementary

85264 V AC without temperature derating
120375 V DC without temperature derating
5060 Hz
TN
Π
ΙΤ
1 mA 240 V AC
Integrated fuse (not interchangeable) 4 A
External protection (recommended) 20 A Curve C
External protection (recommended) 13 A Curve C
30.0 A at 115 V
60.0 A at 230 V
0.55 at 115 V AC
0.45 at 230 V AC
85 % at 115 V AC
88 % at 230 V AC
2228 V
25 W
< 2.5 A 115 V AC
< 1.4 A 230 V AC
< 1.3 A 140 V DC
<1s
> 20 ms 115 V AC
> 40 ms 230 V AC
8000 μF

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Residual ripple	< 120 mV	
Meantime between failure [MTBF]	700000 h at 25 °C, full load conforming to SR 332	
Output protection type	Against overload and short-circuits, protection technology: automatic reset Against over temperature, protection technology: manual reset Against overvoltage, protection technology: manual reset	
Connections - terminals	Screw connection: 0.54 mm², (AWG 20AWG 12) without wire end ferrule for output Screw connection: 0.52.5 mm², (AWG 20AWG 14) with wire end ferrule for output Screw connection: 0.754 mm², (AWG 18AWG 12) without wire end ferrule for input Screw connection: 0.754 mm², (AWG 18AWG 12) with wire end ferrule for input	
Line and load regulation	< 0.5 % at 0 to 100 % load at 25 °C < 1 % at full voltage range in line at 25 °C	
Status LED	1 LED (green) output voltage	
Depth	117.6 mm	
Height	123.6 mm	
Width	40 mm	
Product weight	0.55 kg	
Output coupling	Parallel Serial	
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 Double-profile DIN rail	
Supply	SELV conforming to IEC 60950-1 SELV conforming to IEC 60204-1 SELV conforming to IEC 60364-4-41	
Dielectric strength	3000 V AC with input to output	
Service life	10 year(s)	
overvoltage category	II	

Environment

Standards	IEC 62368-1
	EN/IEC 61204-3
	IEC 61000-6-1
	IEC 61000-6-2
	IEC 61000-6-3
	IEC 61000-6-4
	IEC 61000-3-2
	EN 61000-3-3
	UL 62368-1
	CSA C22.2 No 62368-1
	UL 508
	CSA C22.2 No 107.1
	EN/IEC 62368-1
Product certifications	CE
	CUL listed
	CUL recognized
	RCM
	CB Scheme
	EAC
	KC
Operating altitude	< 5000 m
Shock resistance	150 m/s² for 11 ms
IP degree of protection	IP20

Ambient air temperature for	-2010 °C with current derating of 2 % per °C mounting position A < 2000 m
operation	-1040 °C without derating mounting position A 115 V AC < 2000 m
	-1050 °C without derating mounting position A 230 V AC < 2000 m
	4070 °C with current derating of 1.67 % per °C mounting position A 115 V AC <
	2000 m
	5070 °C with current derating of 2.5 % per °C mounting position A 230 V AC <
	2000 m
Electrical shock protection class	Class I
pollution degree	2
Vibration resistance	3 mm (f= 29 Hz) conforming to IEC 60068-2-6
	10 m/s² (f= 9200 Hz) conforming to IEC 60068-2-6
Electromagnetic immunity	Immunity to electrostatic discharge - test level: 8 kV (contact discharge) conforming to IEC 61000-4-2
	Immunity to electrostatic discharge - test level: 15 kV (air discharge) conforming to IEC 61000-4-2
	Immunity to conducted RF disturbances - test level: 15 V/m (80 MHz2 GHz) conforming to IEC 61000-4-3
	Immunity to conducted RF disturbances - test level: 5 V/m (22.7 GHz) conforming to IEC 61000-4-3
	Immunity to conducted RF disturbances - test level: 5 V/m (2.76 GHz) conforming to IEC 61000-4-3
	Immunity to fast transients - test level: 4 kV (on input-output) conforming to IEC 61000-4-4
	Surge immunity test - test level: 4 kV (between power supply and earth) conforming to IEC 61000-4-5
	Surge immunity test - test level: 3 kV (between phases) conforming to IEC 61000-4-5
	Immunity to conducted RF disturbances - test level: 15 V (0.1580 MHz) conforming to IEC 61000-4-6
	Immunity to magnetic fields - test level: 30 A/m (5060 Hz) conforming to IEC 61000-4-8
	Immunity to voltage dips conforming to IEC 61000-4-11
	Disturbing field emission conforming to EN 55016-2-3
	Limits for harmonic current emissions conforming to IEC 61000-3-2
	conforming to EN 55016-1-2
	conforming to EN 55016-1-2 conforming to EN 55016-2-1
Electromagnetic emission	Conducted emissions conforming to IEC 61000-6-3
	Radiated emissions conforming to IEC 61000-6-4
	Tradiated Smissions Comomiling to IEO 01000-0-4

Packing Units

r aciming Critic	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	17.500 cm
Package 1 Length	18.000 cm
Package 1 Weight	710.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	13
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.948 kg
Unit Type of Package 3	P12
Number of Units in Package 3	312
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm

Package 3 Weight

252.000 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1082
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	698d9b2a-7a6a-4b8f-a149-489156f55645
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No

ABLS1A24050


Dimensions Drawings

Electrical Safety

- If the unit is use in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired.
- For means of disconnection a switch or circuit breaker, located near the product, must be included in the
 installation. A marking as disconnecting device for the product is required.
- The device has an internal fuse. The unit is tested and approved with branch circuit protective device up to 20A. This circuit breaker can be used as disconnecting device.
- The power supply is only suitable for audio, video, information, communication, industrial and control equipment.

Dimensions


Front and Side Views



Connections and Schema


Connections and Schema

Correct Parallel Connection



(1): Load


Incorrect Parallel Connection



(1): Load ABLx1Axxxxx-1 = ABLx1Axxxxx-2 max 2 x ABLx1Axxxxx L1 = L2 Δ V max 25 mV I_{Load} < 90% 2 x I_{nom}

Output Voltage Balancing

ABLS1A24050




(1): R_{Load1}

(2): R_{Load2}

 $R_{Load1} = R_{Load2}$

 $I_1 = I_2 = \sim I_{nom}$

Series Connection



(1): V_{out1}

(2): V_{out2}

(3) : 2 x Diode, V_{RRM}> 2 x V_{out1/2}, I_F > 2 x I_{nom1/2}

(4): V_{Load} = 2 x V_{out}

(5) : Load

Connections and Schema


	(1)		
	<40°C	<50°C	<70°C
ABLS1A24021	50°C	60°C	75°C
ABLS1A24038	50°C	60°C	75°C
ABLS1A12062	50°C	60°C	80°C
ABLS1A24031	50°C	60°C	80°C
ABLS1A12100	60°C	70°C	90°C
ABLS1A24050	60°C	70°C	90°C
ABLS1A48025	60°C	70°C	90°C
ABLS1A24100	60°C	70°C	90°C
ABLS1A24200	95°C	95°C	90°C

(1): Ambient


Mounting and Clearance


Mounting

Mounting Position A




Mounting Position B







Incorrect Mounting

ABLS1A24050










ABLS1A24050


Performance Curves

Performance Curve

Mounting Position A



Mounting Position B



- X : Surrounding Air Temperature (°C)
- Y: Percentage of Maximum Load (%)
- 1 : Altitude \leq 2000 m (6561 ft), Input voltage = 230 VAC / 325 VDC
- 2 : Altitude ≤ 2000 m (6561 ft), 115 VAC / 162 VDC
- $\bf 3$: Altitude \leq 5000 m (16404 ft), Input voltage = 230 VAC / 325 VDC
- 4 : Altitude \leq 5000 m (16404 ft), 115 VAC / 162 VDC