

Product datasheet

Specifications



APC Easy UPS, 2200VA, Tower, 230V, 4x CEE 7/3 Schuko outlets, AVR

BVX2200LI-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	Schuko
Cos phi	0.54
Input voltage limits	140...300 V 230 V AC
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	1200 W
rated power in VA	2200 VA
Output connection type	4 Schuko
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1200 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Half load runtime	00:08:30 600 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains

Graphs

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Complementary

Battery capacity	9.0 Ah
Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Surge energy rate	273 J
Cable length	1.2 m
Number of cables	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Colour	Black
Height	190 mm
Width	140 mm
Depth	390 mm
Product weight	12.2 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Mounting mode	Desktop installation compact
Provided equipment	User manual
Max runtime	240 min
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	40 dBA
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0

Battery recharge time	8 h
-----------------------	-----

Battery life	2...3 year(s)
--------------	---------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	29.7 cm
------------------	---------

Package 1 Width	49.5 cm
-----------------	---------

Package 1 Length	23.5 cm
------------------	---------

Package 1 Weight	13.2 kg
------------------	---------

SCC14	10731304404627
-------	----------------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

Ef3b165e-8e1d-4ef1-89c3-03b78b282225

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

