







Product Code


STAR RMR

General Specifications

Product type	: LED Downlight
Mounting type	: Recessed
Description	: Star LED Slim Recessed Downlight is designed to Provide
	an easy and quick downlight solution without the traditional
	frame, reflector and trim. Perfect for replacing existing
	luminaries & installation in new construction, Available in
	multiple diameters for versatile use across multiple applications.
Category	: Indoor light
Applications	: Offices, schools, hospitals, hotels, retail and residential.

Соlог

Matt White



LED

High Efficiency **IP20**

IP44

F

30,000 HOURS

Lighting Specifications

Model	Watt	lumen	Efficacy(lm/w)	P.F	CRI	ССТ (К)	Lifetime(H)
Star RMR 4	4	300	≥ 75	0.9	≥ 80	3000-6500	30,000
Star RMR 9	9	675					
Star RMR 12	12	900					
Star RMR 20	20	1500					

Physical Specifications

Body: High pressure die-cast aluminumFinishes: Electrostatic paintingDiffuser: PMMA / PCThermal Dissipation: Passive

Electrical Specifications

Driver Driver mounting Voltage Frequency : Included : Separated : 100-240 VAC : 50 Hz

Optical Specifications

Aiming Light distribution Light emission Beam angle : Fixed : Symmetric : Direct : 120°

Applications











ELSEWEDY CATALOGUE 2019