# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# OptiLine 45 - screed floor box - without modules

ISM50330

### Main

Cabling installation system	Floor box
product type	Screeded floor box
Type of floor	Screeded floor
Floor box shape	Rectangular
colour	Light grey
quantity package 1 / unit	1 piece

### Complementary

Fixing mode	Cast-in
Number of modules	Without modules
product material	PP (polypropylene)
Length	265 mm
Height	7595 mm
Width	188 mm

### **Environment**

Standards	73/23/EEC 93/68/EEC IEC 61084-1:ed. 1, 1991 IEC 61084-2-2:2003
operating temperature	-2560 °C
IP degree of protection	IP20

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.500 cm
Package 1 Width	21.500 cm
Package 1 Length	29.500 cm
Package 1 Weight	823.000 g
Unit Type of Package 2	P12
Number of Units in Package 2	120
Package 2 Height	112.000 cm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	111.720 kg

# **Contractual warranty**

Warranty 18 months

# **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	90215406-b6bf-44f8- b463-8540d32a6f6b
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No