

ammeter, GoLogic panel meter, DM1115, single phase

METSEGLDM1115

Main

Range	Go Series
product name	GoLogic DM1000
Device short name	DM1115
Product or component type	Ammeter
Device application	Control Motor control Power distribution Panel installation

Complementary

Poles description	1P + N	
Type of measurement	Current	
[Us] rated supply voltage	48250 V AC +/- 10 % 48250 V DC +/- 10 %	
Supply frequency	50/60 Hz +/- 5 Hz	
Network frequency	50 Hz 60 Hz	
Maximum power consumption in VA	3 VA at 240 V AC	
Display type	LED	
Display digits	4	
Full scale display	999.9	
Control type	Key built-in	
Analogue input type	Current 05 Asingle phase	
Measurement current	1/5 A, 506000 mA AC, 50/60 Hz +/- 5 Hz	
Accuracy	Current +/- 0.5 % of full scale for class 0.5	
Device mounting	Flush	
Mounting support	Panel	
Type of installation	Indoor	
Measurement category	Category III	
Standards	IEC 61326-1	
Product certifications	CE conforming to IEC 61010-1	

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electromagnetic compatibility	Conducted and radiated emissions class A conforming to CISPR 11	
Electromagnetic compatibility	Electrostatic discharge conforming to IEC 61000-4-2	
	Electrical fast transient/burst immunity test conforming to IEC 61000-4-4	
	Surge immunity test conforming to IEC 61000-4-5	
	Conducted RF disturbances conforming to IEC 61000-4-6	
	Magnetic field at power frequency conforming to IEC 61000-4-8	
	Voltage dips and interruptions immunity test conforming to IEC 61000-4-11	
	Harmonics conforming to IEC 61000-3-2	
	Limitation of voltage changes, voltage fluctuations and flicker in low-voltage	
	conforming to IEC 61000-3-3	
	Immunity to radiated fields conforming to IEC 61000-4-3	
	inimumity to radiated fields combining to IEC 01000-4-5	
IP degree of protection	Front panel: IP51 conforming to IEC 60529	
	Body: IP30 conforming to IEC 60529	
Relative humidity	595 %	
pollution degree	2	
Ambient air temperature for operation	-1060 °C	
•		
Ambient air temperature for storage	-2570 °C	
Colour	0	
Colour	Grey	
Width	96 mm	
Height	96 mm	
Depth	43.5 mm	
Cut-out dimensions	92 x 92 mm	
Net weight	175 g	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Unit Type of Package 1 Number of Units in Package 1	PCE 1	

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	11.2 cm
Package 1 Length	12.4 cm
Package 1 Weight	265 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.89 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Ca6cc031-7bcf-4cb9-9e6f-4ddbcf2cdcde
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins