

Product datasheet

Specifications



Mureva Styl - socket-outlet - 16A - 2P + E - shutters - grey

MUR36034

Main

Range	Mureva Styl
Range Of Product	Mureva Styl
Product Or Component Type	Socket-outlet
Device Presentation	Complete product
Outlet Poles Configuration	2P + E
Outlet Standard Description	Side earth
Outlet Standard	Schuko
Colour Tint	Grey (RAL 7016)

Complementary

Device Mounting	Surface
Socket Number	1
Rated Current	16 A
[Ue] Rated Operational Voltage	250 V AC
Condition Of Use	Indoor/outdoor
Material	Brass PC (polycarbonate) PP (polypropylene)
Fixing Mode	By screws
Clamping Connection Capacity	1...2.5 mm ² for rigid cable(s) 1...2.5 mm ² for stranded cable(s) 1...2.5 mm ² for flexible cable(s)
Wire Stripping Length	13 mm
Cable Entry	Easy valve access diameter: 6...12 mm
Height	76 mm
Width	76 mm
Depth	64 mm
Chemical And Detergent Products Resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Quality Labels	EAC AENOR
Ip Degree Of Protection	IP55
Ik Degree Of Protection	IK08
Flame Retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient Air Temperature For Operation	-5...40 °C
Ambient Air Temperature For Storage	-25...55 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	7.500 cm
Package 1 Length	7.500 cm
Package 1 Weight	130.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	8.000 cm
Package 2 Width	16.000 cm
Package 2 Length	39.500 cm
Package 2 Weight	1.393 kg
Unit Type Of Package 3	S04
Number Of Units In Package 3	60
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	9.078 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations