Specifications



Emergency luminaire, Exiway Light, Standard, selectable duration, 110lm, IP42, white

OVA44010

Main

Range	Exiway	
product name	Exiway Light	
Product or component type	Emergency luminaire	
Device application	Anti-panic lighting	
Function	Standard	
Operational mode	Maintained Non-maintained	
Number of batteries	1 x 3.2 V 0.57 Ah LiFePO4	
Colour tint	White	
Light source	9 x LED 0.3 W	
Visibility distance	20 m	
Light source colour	Neutral	
Wiring device additional information	2 wires connection	

Complementary

Device mounting	Surface
Mounting support	Wall
	Ceiling
[Ue] rated operational voltage	230 V AC 50/60 Hz
Power consumption in VA	11.5 VA non-maintained
	11.1 VA maintained
Power consumption in W	0.4 W non-maintained
	0.8 W maintained
Electrical insulation class	Class II
LED lifespan	100000 h
Test function	Manual
Autonomy	1 h
	1.5 h
	2 h
	3 h
Charging time	12 h
Luminous flux	Emergency condition: 110 lm for 1 h
	Emergency condition: 90 lm for 1.5 h
	Emergency condition: 70 lm for 2 h
	Emergency condition: 50 lm for 3 h
	Maintained mode: 70 lm

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Local signalling	LED
Material	Polycarbonate self-extinguishing
Height	112 mm
Depth	32 mm
Width	229 mm
Net weight	0.34 kg

Environment

IP degree of protection	IP42
IK degree of protection	IK09
Fire resistance	850 °C
Product certifications	CE ENEC
Ambient air temperature for operation	040 °C
Standards	EN 60598-1: II EN 60598-2-22 EN 62471 UL 94 V2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	12.000 cm
Package 1 Length	23.500 cm
Package 1 Weight	384.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.306 kg

Contractual warranty

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

P Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

${\ensuremath{\otimes}}$ Materials and Substances		
EU RoHS Directive	Compliant	
Use Again		

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product datasheet

Photometric Diagram

