

Easy UPS On-Line SPM 2000VA 1800W 230V, Turkey

SPM2KI-TR

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V 240 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	1900 W	
Rated power in VA	2000 VA	
Input Connection Type	Schuko	
output connection type	2 Schuko	
Cable length	1.50 m	
Number of cables	1	
Provided equipment	IEC 60320 C13 to Schuko power cable USB cable RS-232 configuration cable user manual	
Range of product	Easy UPS 1Ph On-Line	

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery type	Lead-acid battery
Battery voltage	48 V
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery charger power	76 W rated

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Replacement battery	APCRBCV204 ☐	
General		
General		
Max runtime	2 min	
Number of power module filled slots	0	
Number of power module free slots	0	
Redundant	No	
Physical		
Colour	Black (RAL 7010)	
Height	23.8 cm	
Width	14.5 cm	
Depth	40 cm	
Net weight	16.8 kg	
Mounting location	Front	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Two post mountable	0	
USB compatible	Yes	
Mounting position	Vertical	
Input		
Input voltage limits	440, 205 V half land	
mpat voitage illilits	110285 V half load 180280 V full load	
Network frequency	4070 Hz auto sensing	
Output		
Maximum configurable power in VA	2000 VA	
Maximum configurable power in W	1900 W	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	
Harmonic distortion	3 %	
UPS type	Double conversion online	
Wave type	Sine wave	

_	_			
Co	nfa	rm	20	~~
CU	HU	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ап	CE

Additional information

Efficiency

Bypass type
Crest factor

Product certifications CE

Environmental

Configurable for 220 : 230 or 240 nominal output voltage

Internal bypass (automatic and manual)

88 % (full load)

3 : 1

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-2050 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	015000 m
Acoustic level	50 dBA
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm	
control panel	Multifunction LCD status and control console	

Surge Protection and Filtering

Surge energy rate 300 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	355 mm
Package 1 Width	525 mm
Package 1 Length	235 mm
Package 1 Weight	18.3 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	8c493f2b-82c6-495f-a54a-f7d594e2b537
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins