

Easy UPS On-Line SPM 3000VA 2700W 230V, Turkey

SPM3KI-TR

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V 240 V	
Output voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	2700 W	
rated power in VA	3000 VA	
Input Connection Type	Schuko	
Output connection type	4 Schuko	
Cable length	1.50 m	
Number of cables	1	
Provided equipment	IEC 60320 C19 to Schuko power cable USB cable RS-232 configuration cable user manual	
Range of product	Easy UPS 1Ph On-Line	

Batteries & Runtime

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Battery type	Lead-acid battery	
Battery voltage	72 V	
Extended runtime	0	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	4 h	
Battery charger power	118 W rated	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Replacement battery	APCRBCV205 □	
General		
Max runtime	2 min	
Number of power module filled slots	0	
Number of power module free slots	0	
Redundant	No	
Physical		
Colour	Black (RAL 7010)	
Height	33.6 cm	
Width	19 cm	
Depth	42.5 cm	
Net weight	25.3 kg	
Mounting location	Front	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Two post mountable	0	
USB compatible	Yes	
Mounting position	Vertical	
1		
Input		
Input voltage limits	110285 V half load 180280 V full load	
Network frequency	4070 Hz auto sensing	
Output		
Maximum configurable power in VA	3000 VA	
Maximum configurable power in W	2700 W	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	
Harmonic distortion	3 %	
UPS type	Double conversion online	
Wave type	Sine wave	
Efficiency	90 % (full load)	
Additional information	Configurable for 220 : 230 or 240 nominal output voltage	
Bypass type	Internal bypass (automatic and manual)	
Crest factor	3:1	

Environmental

Conformance
Product certifications

CE

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-2050 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	015000 m
Acoustic level	50 dBA
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate 300 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.5 cm
Package 1 Width	56.5 cm
Package 1 Length	32.5 cm
Package 1 Weight	27.6 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	8c493f2b-82c6-495f-a54a-f7d594e2b537
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

SPM3KI-TR

Image of product / Alternate images

Alternative



