

# UT505 SERIES

## HANDHELD INSULATION RESISTANCE TESTERS



UT505 series handheld true RMS insulation resistance testers combine features of a digital multimeter and insulation resistance tester. Aside from the typical multimeter functions, these meters can also measure insulation resistance, PI, DAR, and automatically calculate resistance ratio to determine the insulation status.

UT505 can be used in insulation resistance testing of precision tools, including motors, cables, transformers, switches, electrical appliances, and insulated materials.

	<b>Range</b>	<b>UT505A</b>	<b>UT505B</b>
Insulation resistance (Ω)	50V	0%~10% ±(3%+5) ±(3%+3)	0%~20% ±(3%+3)
	100V	1GΩ~10GΩ 0.01MΩ~100MΩ 100MΩ~1GΩ	±(10%+3) ±(3%+3) ±(3%+3)
	250V	1GΩ~20GΩ 0.01MΩ~200MΩ 200MΩ~1GΩ	±(10%+3) ±(1.5%+5) ±(1.5%+5)
	500V	1GΩ~50GΩ 0.01MΩ~500MΩ 500MΩ~1GΩ	±(10%+3) ±(1.5%+5) ±(1.5%+5)
	1000V	1GΩ~100GΩ 0.1MΩ~2000MΩ 2GΩ~9.9GΩ 10GΩ~20GΩ 20GΩ~200GΩ	±(10%+3) ±(1.5%+5) ±(10%+3) ±(20%+10) ±(20%+3)
	Load current	50V (R=50kΩ) 1mA 100V (R=100kΩ) 1mA 250V (R=250kΩ) 1mA 500V (R=500kΩ) 1mA 1000V (R=1MΩ) 1mA	0%~10% 0%~10% 0%~10% 0%~10% 0%~10%
	Short circuit current	<2mA	<2mA
Leakage current (A)	10~2000μA		±(10%+3)
Low resistance (Ω)	0.01Ω~20kΩ (about 5V/>200mA) 0.01Ω~100Ω (about 5V/>200mA/20mA optional)	±(1.5%+3)	±(1.5%+3)
General resistance (Ω)	0.01kΩ~10MΩ		±(3%+3)
DC voltage (V)	0V~600V	±(2%+3)	±(2%+3)
AC voltage (V)	0V~600V	±(2%+3)	±(1.5%+5)
Frequency (Hz)	45~1kHz		±(0.1%+3)
Capacitance (F)	100pF~500μF		±(5%+5)
Display count		6000	6000
<b>Features</b>			
Step voltage		✓	✓
Auto power off		✓	✓
Auto range		✓	✓
LCD backlight		✓	✓
Data hold		✓	✓
Low battery indication		✓	✓
Compliance standard	IEC 61557; 61557-1:2007; 61557-2:2007; 61557-4:2007		
Power	1.5V battery (LR6) x 6		
Display	78mm x 59mm		
Product color	Red and grey		
Product net weight	630g		
Product size	103mm x 225mm x 59mm		
Std. accessories	Batteries, test leads, test probes, alligator clips		
Std. individual packing	Carrying bag, gift box, English manual		
Std. quantity per carton	5pcs		
Std. carton measurement	325mm x 320mm x 205mm		
Std. carton gross weight	UT505A: 5.5kg; UT505B: 6.3kg		
Optional accessory	Remote test lead		



● UT505A

- Analog bar graph
- True RMS
- DARPI/Timing measurement
- Comparison measurement
- Auto fuse check (UT505B)
- High voltage output alarm
- Auto discharge
- Continuity buzzer
- 99-group data storage

