

# Product datasheet

Specifications



## pendant control station XAC-A - 5 pushbuttons 1 Emergency stop

XACA6913

### Main

Range Of Product	Harmony XAC
Product Or Component Type	Pendant control station
Device Short Name	XACA

### Complementary

Control Station Type	Double insulated
Enclosure Material	Polypropylene
Electrical Circuit Type	Control circuit
Enclosure Type	Complete ready for use
Control Station Application	Control of 2-speed hoist motor
Control Station Composition	7 push-buttons + 1 emergency stop
Control Button Type	Emergency stop push-button Ø 40 mm 1 NC trigger action blank First push-button 1 NC + 1 NO + 1 NO raise, slow-fast Second push-button 1 NC + 1 NO + 1 NO lower, slow-fast Third push-button 1 NC + 1 NO + 1 NO left, slow-fast Fourth push-button 1 NC + 1 NO + 1 NO right, slow-fast Fifth push-button 1 NC + 1 NO + 1 NO forward, slow-fast
Product Compatibility	ZB2BE102 for emergency stop ZB2BE102 + ZB2BE101 for each direction XENG1191
Mechanical Interlocking	With mechanical interlocking between pairs
Control Station Colour	Yellow
Connections - Terminals	Screw clamp terminals, 1 x 0.5...1 x 2.5 mm <sup>2</sup> without cable end Screw clamp terminals, 1 x 0.5...2 x 1.5 mm <sup>2</sup> with cable end
Standards	IEC 60947-5-1 IEC 60204-32 CSA C22.2 No 14 UL 508 IEC 60947-5-5 EN/ISO 13850: 2006
Product Certifications	CCC GOST
Protective Treatment	TH
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-40...70 °C
Vibration Resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock Resistance	100 gn conforming to IEC 60068-2-27
Overvoltage Category	Class II conforming to IEC 61140

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ip Degree Of Protection</b>	IP65 conforming to IEC 60529
<b>Ik Degree Of Protection</b>	IK08 conforming to IEC 62262
<b>Mechanical Durability</b>	1000000 cycles
<b>Cable Entry</b>	Rubber sleeve with stepped entry 8...26 mm
<b>Contact Code Designation</b>	A600 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 60947-5-1 appendix A A600 AC-15, Ue = 600 V, Ie = 1.2 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 600 V, Ie = 0.1 A conforming to IEC 60947-5-1 appendix A
<b>[Ithe] Conventional Enclosed Thermal Current</b>	10 A
<b>[Uij] Rated Insulation Voltage</b>	Emergency stop contact: 400 V (pollution degree 3) conforming to IEC 60947-1 600 V (pollution degree 3)
<b>[Uimp] Rated Impulse Withstand Voltage</b>	6 kV conforming to IEC 60947-1
<b>Contact Operation</b>	Slow-break
<b>Maximum Resistance Across Terminals</b>	25 MOhm
<b>Operating Force</b>	13 N push-button 14 N emergency stop
<b>Short-Circuit Protection</b>	10 A fuse protection by cartridge fuse type gG
<b>Rated Operational Power In W</b>	40 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 120 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 48 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 48 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 65 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 24 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C
<b>Terminals Description Iso N°1</b>	(13-14)NO (11-12)NC
<b>Terminals Description Iso N°2</b>	(31-32)NC (11-12)NC (21-22)NC
<b>Terminal Identifier</b>	(11-12)NC (13-14)NO
<b>Net Weight</b>	0.97 kg

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	10.0 cm
<b>Package 1 Width</b>	11.0 cm
<b>Package 1 Length</b>	70.0 cm
<b>Package 1 Weight</b>	1.271 kg
<b>Unit Type Of Package 2</b>	P06
<b>Number Of Units In Package 2</b>	25
<b>Package 2 Height</b>	75.0 cm
<b>Package 2 Width</b>	80.0 cm
<b>Package 2 Length</b>	60.0 cm
<b>Package 2 Weight</b>	39.775 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile**

No need of specific recycling operations